

LANMASTER metal 19" drawer optical enclosure, 1U, for 24 SC adapters

Product Code: [LAN-FOBM-RMS-24SC](#)

LANMASTER metal 19" drawer optical enclosure, 1U, for 24 SC adapters



Description

The enclosure is intended for installation in a 19" cabinet or rack and accommodate 24 SC simplex adapters (or duplex LC).

A sliding internal shelf provides easy access to the contents of the enclosure after it is installed in a cabinet.

Cable entries (4 pcs) are located at the rear of the enclosure and covered with rubber grommets. Clamps for the cable and a fastener for the central strength member of the optical cable are installed in the housing.

There are managers for organizing and storing the cable excess in the housing on the sides of the splice tray. Due to that the fiber optic cable in the optical enclosure is not pinched, not twisted, the necessary bending radius of the optical fiber are ensured.

Adapters in the enclosure faceplates can be additionally fasten with special screws. The unused holes of the adapter faceplates can be fitted with rubber plugs, LAN-FPBP-SC product code.

Kit includes:

- Enclosure with 2 splice trays - 1 pc
- Manager for cable excess - 2 pcs
- Cable tie 200 mm - 6 pcs
- M6 screw with cage nut - 4 pcs
- Screws for fasten adapters - 50pcs

Cable entry hole diameter - 20 mm

Made of 1.2 mm steel.

Powder coated.

Color is black (RAL9004).

Dimensions (DxWxH): 340 mm x 230 mm x 44 mm

Enclosure specifications

Dimension	Fiber, max.	Adapters	Splice trays
1U	48	24SC(48LC)	2

Model range

LAN-FOBM-RMS-24SC	LANMASTER metal 19" drawer optical enclosure, 1U, for 24 SC adapters
-------------------	--

Product descriptions are listed according to the available information at the time of publication. Product specifications can be changed without advanced notification. More detailed and exact information can be obtained from the official partners and distributors of LANMASTER.