

22.5x45 Mosaic insert, RJ-45 STP, category 5e, with shutter and enlarged label field, white



Product Code: [LAN-SIP-22S5E-WH](#)

22.5x45 Mosaic insert, RJ-45 STP, category 5e, with shutter and enlarged label field, white

Description

Single-port telecommunication Mosaic inserts (22.5x45) are intended for termination data cables on them. There are contacts for connecting cable conductors on the back side of the module. The contacts of the data socket are covered with a sliding shutter on the front side of the insert. The insert has an enlarged label field covered with a transparent cover. Category 5e compliant.

The insulation displacement contact (IDC) method is used to connect the cables. The cable wires are laid out in grooves on the module lid, and, if necessary, cut off. When you close the lid and turn the mechanism in the latch, the contacts cut through the conductor insulation. Thus, the cable termination can be easily accomplished without the use of tools. The lid is color coded to match the T568A and T568B wire diagrams.

The insert has shielded module. The continuity of the screen is ensured by a metal element in the locking mechanism, as well as a locking cover on the back. The cover has a recess for the incoming cable. The recess allows you to maintain the correct bend radius. The cover can be turned in the desired direction for cable entry from the left or right side.

The depth of the inner part of the module is 32 mm.

Model range

LAN-SIP-22S5E-WH	22.5x45 Mosaic insert, RJ-45 STP, category 5e, with shutter and enlarged label
------------------	--

	field, white
--	--------------

Product descriptions are listed according to the available information at the time of publication. Product specifications can be changed without advanced notification. More detailed and exact information can be obtained from the official partners and distributors of LANMASTER.