


TWT FTP cable, XS series, 25 pairs, category 5e, PVC, grey, 305 meters on a reel

Product Code: [TWT-5EFTP25-XS](#)

TWT FTP cable, XS series, 25 pairs, category 5e, PVC, grey, 305 meters on a reel



Description

The multipair shielded cable is designed for transmission voice and CCTV signals on frequencies below 100 MHz. The cable comprises 25 pairs of solid copper conductors. Outer jacket is PVC.

Each conductor is covered with HDPE (high density polyethylene) insulation. Two conductors are twisted with specially selected step in a single twisted pair.

Twisted pairs are gathered around a strength core element, and covered with a single PVC jacket.

There is a ripcord under the cable jacket for termination process convenience.

The cable is delivered on reels by 305 meters. Other construction lengths are available by order.

Specification	Value
Jacket Color	Grey
Jacket Material	PVC (polyvinyl chloride)
Insulation Material	HDPE (high density polyethylene)
Conductor Type	Solid
Conductor Gauge	24 AWG
Shield material	Aluminum foil
Nominal Velocity Propagation (NVP)	66%
Cable Diameter	11.3 ±1.0 mm
Cable Length per Reel	305 m
Operating Temperature	-20 °C to 75 °C

Model range

TWT-5EFTP25-XS	TWT FTP cable, XS series, 25 pairs, category 5e, PVC, grey, 305 meters on a reel
----------------	--

Product descriptions are listed according to the available information at the time of publication. Product specifications can be changed without advanced notification. More detailed and exact information can be obtained from the official partners and distributors of LANMASTER.